

VG-69

VG-69* organophilic clay is a viscosifier and gelling agent used in Versa* oil base and Nova* synthetic-base systems.

This amine-treated bentonite is used to increase carrying capacity and suspension properties, providing support for weight materials and improved cuttings removal. VG-69 viscosifier also aids in filter-cake formation and filtration control.

Typical Physical Properties

Physical appearance	Off-white to tan powder
Bulk density	528 g /cm3
Specific Gravity.....	1.57

Applications

VG-69 viscosifier is used to increase viscosity and gel strengths in Versa oil-base and NoVa synthetic-base systems. It has proven effective in drilling, coring, workover and completion fluids. The product is also effective in specialty applications such as casing packs, packer fluids and spotting fluids. Good agitation and sufficient shear are required to develop viscosity when using VG-69 viscosifier to build fresh mud.

Typical concentrations range from 2 to 10 lb/bbl (5.7 to 28.5 kg/m³) for most drilling fluid applications, depending on the base fluid and system requirements. Mineral oils generally require higher concentrations than diesel oils. VG-69 viscosifier will not fully yield by the shear and temperature exposure in a mixing plant or mud pit. Care should be taken not to overtreat with VG-69 viscosifier until the fluid has actually circulated through the well. For system maintenance, VG-69 viscosifier should be added as needed to maintain the flow properties and gel strengths in the desired ranges. Specialty applications such as packer fluids and casing packs typically use concentrations in the 10 to 15 lb/ bbl (28.5 to 43 kg/m³) range.

Advantages

- Provides gel structure and viscosity for the suspension of weight materials
- Increases viscosity for improved hole-cleaning capacity
- Improves filter-cake quality and filtration characteristics
- Effective gelling agent in casing packs and packer fluids

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere
 Gamle Forusvei 43
 N-4033 Stavanger,
 Norway
 Phone: +47-51-57-73-00
 Fax: +47-51-57-74-51

Western Hemisphere
 P.O. Box 42842
 Houston, Texas 77242-2842
 Phone: 281-561-1300
 Fax: 281-561-1441
 www.miswaco.slb.com



A Teniz Service M-I SWACO Enterprise



Toxicity and Handling

Information on biological data can be provided upon request.

Handle in accordance with the Material Safety Data Sheet (MSDS) and general requirements for working with industrial reagents

CAUTION! VG-69 viscosifier contains crystalline silica, the inhalation of which may cause cancer.

Packaging and Storage

VG-69 viscosifier is packaged in 50-lb (22.7-kg) and 55.1-lb (25-kg), multi-wall, paper sacks.

Store in a dry, well-ventilated area. Keep container closed. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere
Gamle Forusvei 43
N-4033 Stavanger,
Norway
Phone: +47-51-57-73-00
Fax: +47-51-57-74-51

Western Hemisphere
P.O. Box 42842
Houston, Texas 77242-2842
Phone: 281-561-1300
Fax: 281-561-1441
www.miswaco.slb.com



A Teniz Service M-I SWACO Enterprise

Schlumberger