

SWA EH

SWA* EH wetting agent is a specialized surfactant to preferentially oil-wet solids in the VERSA* oil-base systems.

SWA EH additive complements the system's normal wetting agents to assist in preventing water-wetting of solids. In certain situations, SWA EH additive has the ability to reverse water-wetting of solids that might occur. SWA EH wetting agent is a powerful additive, and provides superior performance when needed.

Typical Physical Properties

Physical appearance	Brown liquid
Specific gravity	1.1
Flash Point.....	75 C

Applications

SWA EH wetting agent can be added to reverse a water-wet solids problem, allowing the surface area of the solids to return to an oil-wet environment. SWA EH will prevent water wetting of all weight material, including FER-OX*.

SWA EH wetting agent may be added to a drilling fluid as a pre-treatment before displacement or cementing jobs are initiated to eliminate any occurrence of water-wetting or used to condition a fluid that has encountered a water-wet problem. In general, for pre-treatment, concentrations of 1 lb/bbl (2.8 kg/m³) are suggested, however if a large amount of open hole is exposed, larger treatments should be considered, but should be limited to no more than 2 lb/bbl (5.6 kg/m³).

Recommended treatment levels for water-wet solids contamination, such as water flows, and CO₂ intrusions, are from 1 to 2 lb/bbl (2.8 to 5.7 kg/m³). Begin treatment as soon as wetting characteristics are observed (graininess, barite settling or flocculation, etc.).

SWA EH wetting agent will assist in preventing sag from water-wet weight material.

During all treatments, normal concentrations of emulsifiers and other additives should be maintained.

In all situations, pilot testing should be done before adding SWA EH wetting agent to insure that over-treatment is avoided.

Advantages

- Prevents water-wet solids
- Reverses water-wet of solids

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere	Western Hemisphere
Gamle Forusvei 43	P.O. Box 42842
N-4033 Stavanger,	Houston, Texas 77242-2842
Norway	Phone: 281-561-1300
Phone: +47-51-57-73-00	Fax: 281-561-1441
Fax: +47-51-57-74-51	www.miswaco.slb.com



A Teniz Service M-I SWACO Enterprise



Limitations

Over-treatment may cause low rheology

Toxicity and Handling

Information on biological data can be provided upon request.

Handle in accordance with the Material Safety Data Sheet (MSDS) and general requirements for working with industrial reagents

Packaging and Storage

SWA EH wetting agent is packaged in 5-gal (18.9-L) cans and 55-gal (208-L) drums.

Store in a dry location away from sources of heat or ignition, and minimize dust.

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere
Gamle Forusvei 43
N-4033 Stavanger,
Norway
Phone: +47-51-57-73-00
Fax: +47-51-57-74-51

Western Hemisphere
P.O. Box 42842
Houston, Texas 77242-2842
Phone: 281-561-1300
Fax: 281-561-1441
www.miswaco.slb.com



A Teniz Service M-I SWACO Enterprise

Schlumberger