OIL-DRI PREMIUM ABSORBENT

OIL-DRI PREMIUM ABSORBENTS undergo a superior moisture extraction process that increases absorption power and minimizes dust. Clay granules are used to absorb oils, mixtures of soluble oils, acids, paints, inks, water and other liquids. Proper use of these products can reduce slipping accidents and hazards, prevent flash oil fires and keep floors clean and dry.

Applications

Potential safety hazards are present around machines or in storage areas where leaks, drips, sprays or spills are most likely to occur.

A spill control plan should be developed with absorbent products readily available to control daily leaks and spills around your plant or to use in case of an emergency.

Advantages

High absorbing capacity

Limitations

Do not use with turpentine, vegetable oil, unsaturated organic compounds or hydrofluoric acid.

Disposal

Oil-Dri products must be disposed of in compliance with local, state and federal regulations. Since various fluids absorbed may be of toxic or hazardous in nature, Oil-Dri does not recommend disposal procedures.

ITEM#	DESCRIPTION	BAGS / PALLET	BAG SIZE	GA WEIGHT	MS WEIGHT	UPC
106032G60	32 Quart Poly Bag	60	24" x 15" x 5"	34 lb.	37 lb.	041788060329
105040G50	40 Quart Poly Bag	50	24" x 17" x 5.5"	42 lb.	46 lb.	041788050405

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.

Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere Gamle Forusvei 43 N-4033 Stavanger,

Norway Phone: +47·51·57·73·00 Fax: 281·561·1441 Fax: +47·51·57·74·51

Western Hemisphere P.O. Box 42842

Houston, Texas 77242-2842 Phone: 281-561-1300

www.miswaco.slb.com



A Teniz Service M-I SWACO Enterprise

