

# Suremul

Suremul\* emulsifier, the primary emulsifier in the Rheliant\* system, provides excellent emulsion stability, referential wetting of solids by the continuous phase, filtration control and temperature stability.

Suremul emulsifier is used in conjunction with Surewet\* secondary emulsifier in the Rheliant system. The Suremul emulsifier can also be used in other nova\* systems as well as the versa\* family of systems in conjunction with a secondary emulsifier or a wetting agent

### Typical Physical Properties

Physical appearance .....Amber liquid  
 Specific gravity .....0.89-0.92  
 Flash Point.....>65C

### Applications

Suremul emulsifier is designed for use as the primary emulsifier in the Rheliant system to provide a stable emulsion and excellent oil wetting.

Suremul emulsifier contributes to HTHP filtration control and to the temperature stability of the system. It is effective over a wide temperature range and in the presence of contaminants. Suremul emulsifier exhibits minimal dispersion tendencies when drilling reactive formations.

Suremul primary emulsifier is used in conjunction with the Surewet secondary emulsifier in the Rheliant system to enhance the emulsion characteristics of the fluid. Suremul emulsifier can also be used as a primary emulsifier in nova systems as well as the Versa family of systems.

Initial system formulations typically require 6 to 10.2 lb/bbl (17 to 29 kg/m3) depending on the desired properties and other components in the system. Daily treatments are usually in the range of 0.1 to 1 lb/bbl (0.3 to 2.85 kg/m3).

For high-temperature applications (temperatures >300°F (150°C)), initial system formulations require 8.75 to 14.0 lb/bbl (25 to 40 kg/m3).

### Advantages

- Improves emulsion stability
- Functions as a secondary wetting agent
- Provides filtration control
- Minimizes dispersion tendencies of reactive clay solids
- Helps maintain HPHT filtrate in a water-free state
- Improves thermal stability and contamination resistance

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere	Western Hemisphere
Gamle Forusvei 43	P.O. Box 42842
N-4033 Stavanger,	Houston, Texas 77242-2842
Norway	Phone: 281-561-1300
Phone: +47-51-57-73-00	Fax: 281-561-1441
Fax: +47-51-57-74-51	www.miswaco.slb.com



A Teniz Service M-I SWACO Enterprise



### Toxicity and Handling

Information on biological data can be provided upon request.

Handle in accordance with the Material Safety Data Sheet (MSDS) and general requirements for working with industrial reagents

### Packaging and Storage

Suremul additive is packaged in a 55-gal (208-L) drum in 550-gal (2131-L) and 275 gal (1000-L) totes.

Store in a dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

This document is supplied solely for informational purposes and M-I LLC makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

Eastern Hemisphere  
Gamle Forusvei 43  
N-4033 Stavanger,  
Norway  
Phone: +47-51-57-73-00  
Fax: +47-51-57-74-51

Western Hemisphere  
P.O. Box 42842  
Houston, Texas 77242-2842  
Phone: 281-561-1300  
Fax: 281-561-1441  
[www.miswaco.slb.com](http://www.miswaco.slb.com)



A Teniz Service M-I SWACO Enterprise

# Schlumberger