

Technical Data: **DURAFLO Composite OEM Screens**

M-I SWACO BEM-6 Shakers

Shaker Brand: M-I SWACO

Compatible with: BEM-6 Series

API Designation	Mesh Type	d ₁₀₀ (cut point, μ)	Conductance (kD/mm)	Non-blanked Area (sq. ft)	Part Number
API 60	XR	244	4.08	5.37	WBM6XR084C
API 70	XR	224	3.54	5.37	WBM6XR105C
API 70	XR	203	3.37	5.37	WBM6XR120C
API 100	XR	144	1.92	5.37	WBM6XR145C
API 100	XR	142	2.5	5.37	WBM6XR165C
API 120	XR	122	2.07	5.37	WBM6XR180C
API 120	XR	118	2.07	5.37	WBM6XR200C
API 140	XR	116	1.55	5.37	WBM6XR230C
API 170	XR	96	0.89	5.37	WBM6XR270C
API 230	XR	62	0.52	5.37	WBM6XR325C
API 230	XR	59	0.45	5.37	WBM6XR400C
API 325	XR	43	0.32	5.37	WBM6XR500C
API 20	XL	800	12.85	5.37	WBM6XL024C
API 35	XL	536	11.64	5.37	WBM6XL038C
API 50	XL	311	6.09	5.37	WBM6XL050C
API 60	XL	273	4.14	5.37	WBM6XL070C
API 70	XL	231	3.69	5.37	WBM6XL084C
API 80	XL	174	2.21	5.37	WBM6XL105C
API 100	XL	142	1.71	5.37	WBM6XL120C
API 120	XL	127	1.45	5.37	WBM6XL150C
API 140	XL	116	1.97	5.37	WBM6XL165C
API 140	XL	102	1.74	5.37	WBM6XL200C
API 170	XL	88	1.07	5.37	WBM6XL220C
API 200	XL	73	1.18	5.37	WBM6XL230C
API 200	XL	70	0.93	5.37	WBM6XL270C
API 230	XL	62	0.51	5.37	WBM6XL325C
API 270	XL	54	0.36	5.37	WBM6XL360C
API 325	XL	48	0.42	5.37	WBM6XL400C

API Designation	Mesh Type	d ₁₀₀ (cut point, μ)	Conductance (kD/mm)	Non-blanked Area (sq. ft)	Part Number
API 60	HC	269	4.39	5.37	WBM6HC084C
API 60	HC	235	4.44	5.37	WBM6HC105C
API 70	HC	202	3.78	5.37	WBM6HC120C
API 80	HC	169	3.3	5.37	WBM6HC165C
API 100	HC	139	2.65	5.37	WBM6HC200C
API 120	HC	120	1.36	5.37	WBM6HC230C
API 170	HC	86	1.03	5.37	WBM6HC270C
API 200	HC	73	0.85	5.37	WBM6HC325C
API 10	MG	2051	52.51	5.37	WBM6MG010C
API 18	MG	962	26.33	5.37	WBM6MG020C
API 30	MG	577	9.61	5.37	WBM6MG030C
API 40	MG	413	7.43	5.37	WBM6MG040C
API 60	MG	243	-	5.37	WBM6MG060C
SNAP-LOK Plugs					WBM6YYZZZ

Screen Specifications

- Dimensions (W x L, inches): 36" x 27.5"
- Weight: 17.6 lbs